

SLIM

Famiglia di paletti dal design elegante e pulito, dallo spessore di soli 36 mm, SLIM è un paletto dalle forme discrete che può essere installato anche a ridosso di pareti e muri, senza creare ingombro. Un insieme di rettangoli compongono il paletto, con il diffusore in vetro sullo stesso piano del corpo completamente a filo. Disponibile in due altezze e con emissione mono e bidirezionale, risulta adatto per camminamenti e vialetti di parchi e giardini.

Family of stalks from clean, elegant design and a thickness of just 36 mm, SLIM is a stalk in discrete forms that can also be installed close to different walls, with no encumbrance. A set of rectangles composes the wicket, with glass diffuser on the same plane of the body completely flush. Available in two heights and with mono and bi-directional emission, it is suitable for walkways and paths of parks and gardens.





INFORMAZIONI TECNICHE

Corpo in lega di alluminio estruso verniciato e resistente alla corrosione. Protezione con trattamento di anodizzazione, fondo con polveri epossidiche e verniciatura poliesteri. Flangia di fissaggio a pavimento completamente scomparsa. Valvola in Gore per impedire la formazione di condensa all'interno del prodotto.

TECHNICAL INFORMATION



Body made of extruded, corrosion resistant, aluminium alloy. Protection with anodizing treatment, epoxy powder base coating and polyester painting. Completely hidden ground fixing flange. Gore valve to prevent condensation inside the product.





**WHITE
COB LED
230V**



50 00 611
LED 3000K COB CRI>80
8W / 1000 lm LED data
8,8W / 700 lm Real data
220-240V 0/50/60Hz
1 opening
Height 500 mm
A / A+ / A++



50 00 612
LED 3000K COB CRI>80
8W / 1000 lm LED data
8,8W / 650 lm Real data
220-240V 0/50/60Hz
2 openings
Height 500 mm
A / A+ / A++




PRODUCT INFORMATION

IP65
IK 08
5 mm thick extra-clear flat tempered glass
Cable input Ø 5,5÷10 mm

AVAILABLE COLOURS
■ .06 grey
■ .08 anthracite
Other colours on request



TECHNICAL DATA





**WHITE
COB LED
230V**



50 10 611
LED 3000K COB CRI>80
8W / 1000 lm LED data
8,8W / 700 lm Real data
220-240V 0/50/60Hz
power supply included
Height 800 mm
A / A+ / A++



50 10 612
LED 3000K COB CRI>80
8W / 1000 lm LED data
8,8W / 650 lm Real data
220-240V 0/50/60Hz
power supply included
Height 800 mm
A / A+ / A++




PRODUCT INFORMATION

IP65
IK 08
5 mm thick extra-clear flat tempered glass
Cable input Ø 5,5÷10 mm

AVAILABLE COLOURS
■ .06 grey
■ .08 anthracite
Other colours on request

TECHNICAL DATA



Disponibile su richiesta senza maggiorazione di prezzo (per la composizione del codice consultare pagina 8)
Available upon request without surcharge (for the code composition, please refer to page 9)

HELP YOU

LED LED COLOURS TEMPERATURE 4000K

Other LED colours available on request

COLORS FINISHES
■ .01 black
■ .02 white
■ .07 corten
■ .09 bronze

ACCESSORI (per maggiori dettagli consultare pagina 321)
ACCESSORIES (for further details please refer to page 321)

FIXING
page 341
89 50 025 - Tie rod

INFO
Ulteriori versioni sono disponibili consultando www.platek.eu

More versions are available on www.platek.eu



More details at: platek.eu/SLIM