

T4 collection

Una famiglia di pali dal design razionalista. T4 è una piccola struttura architettonica luminosa: il corpo a sezione quadrata è composto da due volumi separati da due montanti che sostengono la fonte luminosa. All'accensione, questa struttura effimera scompare alla vista, trasformandosi in due fasci di luce geometrica che creano sul pavimento una suggestiva alternanza di luce e di ombra. T4 è un efficiente apparecchio per l'illuminazione di spazi aperti, aree pedonali e per l'arredo urbano.

A family of poles by the rationalist design. T4 is a small architectural lighting structure: the body with a square section is composed of two separate volumes by two uprights supporting the light source. At power-on, this ephemeral structure disappears from sight, transforming into two beams of geometrical light which creates a suggestive alternation of light and shadow on the floor. T4 is an efficient tool for the lighting of open spaces, pedestrian areas and urban zones.





INFORMAZIONI TECNICHE

Corpo in lega di alluminio estruso verniciato e resistente alla corrosione. Testa realizzata in pressofusione di alluminio verniciato e resistente alla corrosione. Protezione con trattamento di anodizzazione, fondo con polveri epossidiche e verniciatura poliester. Viti in acciaio inox A4.

TECHNICAL INFORMATION

Body made of extruded, corrosion resistant, aluminium alloy. Head made in corrosion resistant and painted die-cast aluminium. Protection with anodizing treatment, epoxy powder base coating and polyester painting. A4 stainless steel screws.




WHITE
COB LED
230V



4 OPENINGS




50 34 611
LED 3000K COB CRI>80
 17W / 2600 lm Nominal data
20,8W / 1830 lm Real data
 220-240V 50/60Hz
Surge protection included
 A / A+ / A++
 Height 1200 mm



diffuse

381
cd/klm



3000K

130 lux
 100 lux
 70 lux
 40 lux
 10 lux

(m)


PRODUCT INFORMATION

IP66
 IK 10
 4 mm anti-glare clear
 PMMA lens
 Cable input Ø 4÷16 mm

AVAILABLE COLOURS

.06 grey
 .08 anthracite
 Other colours on request

TECHNICAL DATA



Disponibile su richiesta senza maggiorazione di prezzo (per la composizione del codice consultare pagina 8)
 Available upon request without surcharge (for the code composition, please refer to page 9)

HELP YOU

LED
 LED COLOURS
 TEMPERATURE
 4000K

Other LED colours
 available on request

COLORS
FINISHES
 .01 black
 .02 white
 .07 corten
 .09 bronze

INFO
 Ulteriori versioni sono
 disponibili consultando
www.platek.eu

More versions are available on
www.platek.eu

ACCESSORI (per maggiori dettagli consultare pagina 321)
ACCESSORIES (for further details please refer to page 321)



FIXING
 page 340
89 50 090 - Tie rod



More details at:
platek.eu/T4


WHITE
COB LED
230V



4 OPENINGS




50 34 612
LED 3000K COB CRI>80
 24W / 3685 lm Nominal data
29,5W / 2450 lm Real data
 220-240V 50/60Hz
Surge protection included
 A / A+ / A++
 Height 2200 mm



diffuse

381
cd/klm



3000K

5

2,5

0

2,5

5

(m)

61 lux
 48 lux
 35 lux
 22 lux
 9 lux

PRODUCT INFORMATION

IP66
 IK 10
 4 mm anti-glare clear
 PMMA lens
 Cable input Ø 4÷16 mm

AVAILABLE COLOURS

.06 grey
 .08 anthracite
 Other colours on request

TECHNICAL DATA



Disponibile su richiesta senza maggiorazione di prezzo (per la composizione del codice consultare pagina 8)
 Available upon request without surcharge (for the code composition, please refer to page 9)

HELP YOU

LED
 LED COLOURS
 TEMPERATURE
 4000K

Other LED colours
 available on request

FINISHES
 .01 black
 .02 white
 .07 corten
 .09 bronze

COLORS

ACCESSORI (per maggiori dettagli consultare pagina 321)
ACCESSORIES (for further details please refer to page 321)



FIXING
 page 340
 89 50 090 - Tie rod

INFO
 Ulteriori versioni sono
 disponibili consultando
www.platek.eu

More versions are available on
www.platek.eu



More details at:
platek.eu/T4

WHITE
COB LED
230V



4 OPENINGS



50 34 614

LED 3000K COB CRI>80

37W / 4900 lm Nominal data


45W / 3320 lm Real data

220-240V 50/60Hz

Surge protection included


A / A+ / A++

Height 3600 mm



diffuse

381
cd/klm



3000K

36 lux
28 lux
20 lux
12 lux
4 lux

PRODUCT INFORMATION

IP66

IK 10

4 mm anti-glare clear

PMMA lens

Cable input Ø 4÷16 mm

AVAILABLE COLOURS

.06 grey

.08 anthracite

Other colours on request

TECHNICAL DATA



Disponibile su richiesta senza maggiorazione di prezzo (per la composizione del codice consultare pagina 8)
Available upon request without surcharge (for the code composition, please refer to page 9)

HELP YOU

LED

LED COLOURS
TEMPERATURE
4000K

Other LED colours
available on request

COLORS

FINISHES

.01 black
.02 white
.07 corten
.09 bronze

ACCESSORI (per maggiori dettagli consultare pagina 321)
ACCESSORIES (for further details please refer to page 321)



FIXING
page 340
89 50 090 - Tie rod

INFO

Ulteriori versioni sono
disponibili consultando
www.platek.eu

More versions are available on
www.platek.eu



More details at:
platek.eu/T4